



NTN BEARUNG DRIVESHAFT, INC.



30 mm x 72 mm x 19 mm SKF 7306 BEGAPH
angular contact ball bearings

Bearing No. 7306 BEGAPH

7306 BEGAPH Bearing 2D drawings and 3D CAD models

Size	72x30x19 mm
Bore Diameter	72 mm
Outer Diameter	30 mm
Width	19 mm
d	30 mm
D	72 mm
B	19 mm
d ₁	46.5 mm
d ₂	37.9 mm
D ₁	56.6 mm
a	31 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
d _a - min.	37 mm
D _a - max.	65 mm
D _b - max.	67.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	35.5 kN
Basic static load rating - C ₀	21.2 kN
Fatigue load limit - P _u	0.9 kN
Reference speed	13000 r/min
Limiting speed	13000 r/min
Calculation factor - k _r	0.1



NTN BEARUNG DRIVESHAFT,INC.

Calculation factor - k_a	1.6
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y_0	0.52
Calculation factor - Y_1	0.55
Calculation factor - Y_2	0.93
Calculation factor - X	0.35
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	PEEK
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Preload	Light
Mounting Arrangement	Universal
Inch - Metric	Metric



NTN BEARUNG DRIVESHAFT,INC.

Long Description	30MM Bore; 72MM Outside Diameter; 19MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; PEEK Cage; 40 Degree; 1 (Single); Li
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Width	0.748 Inch 19 Millimeter
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
d_1	46.5 mm
d_2	37.9 mm
D_1	56.6 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	37 mm
D_a max.	65 mm
D_b max.	67.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	35.5 kN
Basic static load rating C_0	21.2 kN
Fatigue load limit P_u	0.9 kN
Calculation factor A	0.0074
Calculation factor k_r	0.1
Calculation factor e	1.14



NTN BEARUNG DRIVESHAFT, INC.

Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.34 kg