



NTN BEARUNG DRIVESHAFT, INC.



71936 ACD/P4A Bearing 2D drawings and 3D CAD models

180 mm x 250 mm x 33 mm SKF 71936
ACD/P4A angular contact ball bearings

Bearing No. 71936 ACD/P4A

Size	250x180x33 mm
Bore Diameter	250 mm
Outer Diameter	180 mm
Width	33 mm
d	180 mm
D	250 mm
B	33 mm
d ₁	201.6 mm
d ₂	201.6 mm
D ₁	228.4 mm
r _{1,2} - min.	2 mm
r _{3,4} - min.	1 mm
a	66.8 mm
d _a - min.	189 mm
d _b - min.	189 mm
D _a - max.	241 mm
D _b - max.	245 mm
r _a - max.	2 mm
r _b - max.	1 mm
d _n	207.4 mm
Basic dynamic load rating - C	159 kN
Basic static load rating - C ₀	200 kN
Fatigue load limit - P _u	5.8 kN
Limiting speed for grease	4800 r/min



NTN BEARUNG DRIVESHAFT, INC.

Lubrication	
Limiting speed for oil lubrication	7000 mm/min
Ball - D_w	22.225 mm
Ball - z	27
G_{ref}	54 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	1000 N
Preload class B - G_B	2000 N
Preload class C - G_C	4000 N
Preload class D - G_D	8000 N
Calculation factor - f	1.25
Calculation factor - f_1	0.98
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.04
Calculation factor - f_{2C}	1.08
Calculation factor - f_{2D}	1.14
Calculation factor - f_{HC}	1
Preload class A	442 N/micron
Preload class B	581 N/micron
Preload class C	774 N/micron
Preload class D	1055 N/micron



NTN BEARUNG DRIVESHAFT,INC.

Category	Precision Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7 ISO P4
Material - Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	25 Degree
Preload	None
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Flush Ground	No
Inch - Metric	Metric
Other Features	Single Row Angular Contact High Capacity Basic Design
Long Description	180MM Bore; 250MM Outside Diameter; 33MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 1 (Single) Bearing; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Ra
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Ball Angular Contact
Manufacturer URL	http://www.skf.com



NTN BEARUNG DRIVESHAFT, INC.

Bore	7.087 Inch 180 Millimeter
Width	1.299 Inch 33 Millimeter
Outside Diameter	9.843 Inch 250 Millimeter
d_1	201.6 mm
d_2	201.6 mm
D_1	228.4 mm
$r_{1,2}$ min.	2 mm
$r_{3,4}$ min.	1 mm
d_a min.	189 mm
d_b min.	189 mm
D_a max.	241 mm
D_b max.	245 mm
r_a max.	2 mm
r_b max.	1 mm
d_n	207.4 mm
Basic dynamic load rating C	159 kN
Basic static load rating C_0	200 kN
Fatigue load limit P_u	5.85 kN
Attainable speed for grease lubrication	4800 r/min
Attainable speed for oil-air lubrication	7000 r/min
Ball diameter D_w	22.225 mm
Number of balls z	27
Reference grease quantity G_{ref}	54 cm ³
Preload class A G_A	1000 N
Static axial stiffness, preload class A	442 N/ μ m
Preload class B G_B	2000 N
Static axial stiffness, preload class B	581 N/ μ m
Preload class C G_C	4000 N
Static axial stiffness, preload	774 N/ μ m



NTN BEARUNG DRIVESHAFT,INC.

class C	
Preload class D G_D	8000 N
Static axial stiffness, preload class D	1055 N/ μ m
Calculation factor f	1.25
Calculation factor f_1	0.98
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.04
Calculation factor f_{2C}	1.08
Calculation factor f_{2D}	1.14
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	4.2 kg